


# Hi-Polamur Sanding Seal

## Description



### Proven Performance

Hi-Polamur Sanding Seal is specifically designed to seal and protect new or freshly sanded wood floors prior to applying Poli-Mirro 450 Finish. Hi-Polamur penetrates and strengthens the wood to provide an excellent base for finish.

### Excellent Sanding Properties

Hi-Polamur Sanding Seal has excellent sanding properties to make a smooth professional appearance on re-finish projects. Hi-Polamur is an oil modified urethane that makes an excellent seal for gymnasiums, commercial and residential wood floor installations. It is easily sanded between coats and prior to applying game lines.

Use Hi-Trac Wood Floor Cleaner to keep floors clean and maintain a high traction surface.



Multi-Clean recommends the following enamel paint for lining when using Hi-Polamur.

#### Benjamin Moore Impervo

Follow specific lining instructions in the Wood Floor Method Bulletin #1420.

#### Learn More.....at [www.multi-clean.com](http://www.multi-clean.com)

- \*Training materials: Multi-Clean Method Bulletin 1406 provides detailed floor care procedures.
- \*Calculators: Easy online calculator provides estimates of product usage for a project.



**VOC Compliant:** Hi-Polamur meets new Federal VOC Regulations for sanding sealers.

#### Properties

|                         |   |
|-------------------------|---|
| Appearance .....        | Amber liquid                            |
| Odor .....              | Solvent odor                            |
| Flashpoint .....        | 104°F                                   |
| % Solids .....          | 40%                                     |
| Slip Resistance .....   | Exceeds 0.5%                            |
| Coverage .....          | 400-600 sq. ft./gal. (recoat)           |
| Dry Time .....          | 4-6 hours<br>17-24 hours before sanding |
| Storage .....           | 1 year under normal conditions          |
| Freeze Thaw .....       | Does not freeze                         |
| VOC (minus water) ..... | Less than 550 grams/liter               |

FOR INDOOR USE ONLY.

#### Packaging

5 gallon, #903325

WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applier. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.

## Multi-Clean®

600 Cardigan Road, Shoreview, Minnesota 55126 Phone 651-481-1900 Fax 651-481-9987 Web [www.multi-clean.com](http://www.multi-clean.com)

12-19-06

1544