


First Round

Waterborne Wood Gym Floor Seal



Waterborne seal for wood floors designed to provide a base for finishes and helps prevent side bonding on tongue and groove flooring.

Penetrating Seal

First Round is specially designed to seal and protect new or freshly sanded wood floors prior to applying finishes.

Two coats of First Round penetrates the wood and provides an excellent base for applying game lines and finish topcoats. First Round is recommended on new or freshly sanded wood flooring prior to using Court Shield Final Floor or ProFloor 100.

Non-Stick Coating

Extensive field experience and testing show First Round is not likely to have an adhesive effect (referred to as "Side Bonding") on nailed down tung and groove flooring. Some finishes cause cracking or board splitting ("panelization") due to the adhesive properties of the coating.

Applies Easily - Dries Fast

First Round goes down fast and easy with the PADCO Professional Floor Coater. The product dries quickly, and can be recoated or lightly screen disk sanded in as little as 2 hours.

The recommended marking enamel for painting game lines on gymnasium floors is Benjamin Moore Impervex Latex Gloss Enamels.



Environmentally Responsible

Learn More.....at www.multi-clean.com

- *Training materials: Multi-Clean Method Bulletin 1406 provides detailed floor care procedures.
- *Calculators: Easy online calculator provides estimates of product usage for a project.



NOTE: Some parquet floors should not be finished with polyurethane coatings. Check with floor manufacturer before using on parquet floors.

Properties

Appearance	Milky, off white
Flashpoint	None
% Solids	26.0 - 26.5
Slip Resistance	Exceeds 0.5 minimum
Coverage	600 - 800 sq. ft./gallon
Dry Time	2 hours
Number of Coats Required	2
Storage Conditions	Heated warehouse
Freeze-Thaw Stability	Passes three cycles
Storage Stability	1 year under normal conditions
VOC (minus water)	Less than 340 grams/liter

FOR INDOOR USE ONLY.

Packaging

1 gallon, #904993

WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applier. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.

Multi-Clean®