

Dilution Control Systems

Sanitation Station Model 421331 3 GPM

Wall mounted, high volume washing, foaming, and or sanitizing proportioner with two product eductors.

Multi-Clean manufactures quality proportioning equipment. Please use this equipment carefully and observe all warnings and cautions.

Note:

Wear protective clothing and eyewear when dispensing chemicals. Always observe safety and handling instructions on product bottle or SDS. Always direct discharge away from you or other persons or into approved container. Clean equipment after each use. Attach only to tap water outlets not exceeding 140°F (60°C) and 125 PSI maximum.

Package includes:

Complete wall mount unit.	1 red discharge hose, 25 ft.
2 cap-hose assemblies.	1 black water supply hose, 6 ft.
4 anchors and screws.	1 spray gun.
1 hose hanger.	1 foamer attachment.

Instructions for installation:

1. Attach hose hanger to bottom of unit.
2. Attach unit to wall using hardware supplied using 1/4" drill bit.
3. Install product draw tubes onto appropriate hose barbs.
5. Connect 1/2" x 6 feet black water inlet hose.
6. Connect 1/2" x 25 feet red discharge hose to bottom of unit.
7. Turn water supply on to unit. 25 PSI minimum required.
8. Turn selector valve to begin dispensing. Only one product can be dispensed at a time.

Installation must conform to local plumbing codes and use approved backflow prevention devices. Unit is not equipped with backflow preventer. Make sure there is an approved backflow device up stream of this unit.

Read precautionary information on product SDS prior to handling. Refer to Food Sanitation Method Bulletin 1427 for complete application instructions online at www.multi-clean.com.



600 Cardigan Road
Shoreview, Minnesota
Phone 651- 481-1900
Fax 651- 481-9987
www.multi-clean.com