

Buff N' Clean

Spray Buff & Clean



BUFF N' CLEAN is a blend of resinous polymers, selected waxes, and detergent in one formulation. It is a fast-acting synthetic detergent with instant penetrating action. Use in spot cleaning of floors, or to retard powdering of floor finishes. The resinous polymers and waxes are durable and can be machine buffed to a high gloss.

It can be used as a cleaning/buffing compound. The detergent acts quickly to penetrate dirt and black marks to lift them off the floor. At the same time, the resinous polymers and waxes seal the area and cover it with a durable coat that buffs to a high shine, thus restoring the original lustre of the floor's appearance. It can also be used as a damp mop treatment on floors with powdering problems. The adhesion ability is such that, in most cases, it will completely stop and, in others, slow down any powdering problem that exists.

BUFF N' CLEAN is intended for use in the daily maintenance of waxed or finished floors for spot cleaning and refinishing those areas or spots which are scuffed, black marked or otherwise heavily soiled. It is gentle and completely safe for all types of floors - asphalt, rubber, vinyl, vinyl composition, linoleum, finished concrete, terrazzo, marble, etc.



Buff N Clean exceeds slip resistance standards when tested according to ASTM D-2047.



Learn More.....at www.multi-clean.com

*Training materials: Multi-Clean Method Bulletin. 1415 provides detailed floor care procedures.

*Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applicator. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.

Properties

Appearance.....White opaque, low viscosity liquid
 pH.....9.3
 Specific Gravity.....1.001 - 1.006
 Flashpoint.....None
 Slip Resistant.....Exceeds 0.5 minimum average static coefficient of friction (James Machine)
 Percent of Free Alkali.....None
 Percent of Oils.....None
 Drying Time.....Approximately 20 minutes
 Storage Temperature.....40°F minimum, 100°F maximum
 Storage Stability.....Excellent, 1 year normal conditions
 Freeze-Thaw Stability.....Possible damage with hard freeze
 VOC Compliance - EPA, IL, IN, MI, OH, OTC, UT, and Canada regulations

Packaging

1 Gallon, 902403



600 Cardigan Road
 Shoreview, Minnesota
 Phone 651-481-1900
 Web www.multi-clean.com