

Premier

High Traffic Floor Finish



Maximum Durability

PREMIER is based upon the most advanced thermoplastic polymer technology that combines gloss with wear properties that go beyond conventional finishes. PREMIER offers the highest durability in a floor finish with exceptional resistance to scuffing and black heel marking.

Brilliant Gloss

The brilliant, crystal clear gloss provided by PREMIER is enhanced with optical brighteners. The optical brighteners absorb non-visible light and re-emit it as visible light, enhancing the brilliance of the finish. Multiple coats of PREMIER can be applied quickly to achieve maximum gloss.

No Buffing Required

PREMIER is a low maintenance finish that is normally not high speed burnished. It is ideal for accounts that maintain floors with simple daily cleaning and periodic recoating. The durability of PREMIER allows the finish to retain gloss longer than other finishes with minimal maintenance. PREMIER can also be spray buffed with a low speed machine using BUFF-N-CLEAN.

The PREMIER Challenge

Compare the durable performance of PREMIER side by side with other finishes and you will see the difference:

- **Less scuffing/markings**
- **Holds shine longer**
- **Requires less recoating**
- **Looks brighter, longer**

The bottom line is floors look better and last longer between recoats and strip outs, saving you time and money.



PREMIER exceeds slip resistance standards when tested according to ASTM D-2047 (James Machine).

Properties

Appearance	Milky white liquid
Finish Type	Extended wear
Non-Volatile (solids).....	20.0
pH.....	8.5 - 9.0
Weight/Gallon	8.61 - 8.68
Slip Resistance.....	Exceeds .5 static coefficient of friction
Coverage	2000 - 3000 sq. ft./gal.
Soil Resistance.....	Excellent
Drying Time	35 - 45 minutes
Color of Dry Film.....	Water clear
Application Temperature.....	50°F (minimum)
Storage Temperature.....	40°F minimum, 100°F maximum
Storage Stability	1 year under normal conditions
Freeze-Thaw Stability.....	Passes three cycles

VOC Compliant - VOC Free

Learn More.....at www.multi-clean.com

- *Training materials: Multi-Clean Method Bulletin 1415 provides detailed floor care procedures.
- *Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applicator. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.



600 Cardigan Road
Shoreview, Minnesota
Phone 651-481-1900
Web www.multi-clean.com



Packaging

- 55 gallon, 904017
- 5 gallon, 904015
- 1 gallon, 904013