

Prime Shine® High Speed Floor Finish



Ultra Gloss Burnishing Finish

Prime Shine was designed specifically for use with ultra high speed burnishing equipment. The product quickly snaps back to a deep, lustrous shine without the need for a restorer. The Ultra Floor Care System will produce spectacular looking floors using propane, battery or electric burnishing equipment.

Designed for Speed

Prime Shine was developed for commercial/retail floors that demand a clear, high gloss-wet look appearance when UHS burnished on a frequent basis. Prime Shine has a sparkling clarity that does not haze over time. The more Prime Shine Ultra is burnished, the higher the gloss...and the product does not swirl or scratch when burnished like softer high speed products.

Stands Tough Against Wear

Prime Shine outwears and outshines softer products that scuff, mark and lose gloss rapidly...yet scratches, and scuffs disappear after burnishing without the use of a restorer.

Prime Shine offers superior burnish response, repairability, scuff and mark resistance to enhance labor productivity and keep floors looking good day after day.

Cleans up on the Competition

Dirt is the natural enemy of high gloss-high traffic floors causing a dingy appearance over time. Soil Shield™ is exclusive technology that makes Prime Shine less compatible with dirt. Soil Shield™ means floors clean-up better and look brighter for longer periods of time.

Designed with
Soil Shield technology!



Learn More.....at www.multi-clean.com

*Training materials: Multi-Clean Method Bulletin 1415 provides detailed floor care procedures.

*Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applier. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.



600 Cardigan Road
Shoreview, Minnesota
Phone 651-481-1900
Web www.multi-clean.com



Prime Shine Ultra exceeds slip resistance standards when tested according to ASTM D-2047.

Properties

Appearance	Milky white
Finish Type	Burnishing finish
Non-Volatile (solids).....	20.5 ± .5
pH	9.0 - 9.3
Weight/Gallon	8.60 - 8.65
Slip Resistance.....	Exceeds 0.5 static coefficient of friction, James Machine
Dry Time	30 - 45 minutes
Color of Dry Film.....	Water clear
Application Temperature.....	50°F (minimum)
Storage Temperature.....	40°F minimum, 100°F maximum
Storage Stability	1 year under normal conditions
Freeze/Thaw Stability	Passes 3 cycles
VOC Compliant - VOC Free	

Packaging

55 gallon, 904937
5 gallon, 904935