

# StoneShield

## Natural Stone Seal Finish



### Maintain

The natural beauty of marble flooring can be effectively maintained and preserved with the StoneShield™ Marble Floor Care Program.

### Protect

Multi-Clean STONESHIELD is formulated to bond to marble and other natural stone floors to provide effective protection against wear, water, soiling and deterioration.

### Durable

STONESHIELD is a durable, high gloss seal/finish that provides a crystal clear, slip resistant coating which enhances the appearance of natural stone. The water clear, protective coating will not detract from the natural beauty and color of natural stone floors.

### Simple

The STONESHIELD method of application and maintenance is simple. Anyone familiar with standard resilient floor care can use STONESHIELD to achieve beautiful natural stone floors. Costly and labor intensive grinding with specialized equipment and/or the use of strong acids for recrystallizing worn marble is effectively eliminated. The STONESHIELD method will allow marble and other natural stone floors to always be maintained at consistently high levels of appearance.



**STONESHIELD exceeds slip resistance standards when tested in accordance with ASTM D2047.**

### Properties

|                                    |  |
|------------------------------------|--|
| Appearance .....                   | Milky, white emulsion                                  |
| pH .....                           | 9.0 - 9.3  |
| Specific Gravity.....              | 1.03 - 1.04  |
| Non-Volatile (solids content)..... | 21.0 - 22.0  |
| Slip Resistance.....               | Exceeds 0.5 min average static coefficient of friction |
| Coverage .....                     | 1500 - 2500 sq. ft./gallon                             |
| Drying Time .....                  | 45 - 50 min (normal conditions)                        |
| Minimum Application Temp.....      | 50°F   |
| Storage Temperature.....           | 40°F minimum, 100°F maximum                            |
| Storage Stability .....            | 1 year under normal conditions                         |
| Freeze - Thaw Stability.....       | Passes 3 cycles  |

VOC Compliant - VOC Free

**Learn More.....at [www.multi-clean.com](http://www.multi-clean.com)**

- \*Training materials: Multi-Clean Method Bulletin 1415 provides detailed floor care procedures.
- \*Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applicator. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.



600 Cardigan Road  
Shoreview, Minnesota  
Phone 651-481-1900  
Web [www.multi-clean.com](http://www.multi-clean.com)

### Packaging

55 gallon, 904957  
1 gallon, 904953