

MATERIAL SAFETY DATA SHEET

(COMPLIES WITH 29CFR 1910.1200)

SECTION I - CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Identity (As Used on Label and List): Multi-Clean Waterless Wood Floor Cleaner
Product Class: Petroleum distillate
Emergency Telephone Number: 800-255-3924
Telephone Number for Information: 651-481-1900
Manufacturer's Name and Address:
Multi-Clean®, A Division of Minuteman International, Inc.
600 Cardigan Road
Shoreview, MN 55126

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components (Specific Chemical Identity):

Chemical	Common Name(s)	%
A	Mineral spirits CAS #8052-41-3	60 - 100

SECTION III - HAZARDS IDENTIFICATION

Emergency Overview

Appearance and Odor: Clear liquid, solvent odor.
Primary Hazards: Harmful or fatal if swallowed. Vapor may be harmful.
Combustible. Irritant.

Potential Health Hazards

Route(s) of Entry: Skin Absorption: X Ingestion: Inhalation: X
Eye: May cause irritation on contact.
Skin: May cause irritation on contact.
Ingestion: May be harmful if swallowed.
Inhalation: Vapor may be harmful.
Signs and Symptoms of Exposure: Eyes and Skin: Irritation, redness. Inhalation: Irritation, central nervous system effects (dizziness, headaches, nausea, etc.).
Carcinogenicity: NTP? No IARC Monographs? No
OSHA Regulated? No

Target Organ (s): Skin, eyes, respiratory system and central nervous system.
Medical Conditions Generally Aggravated by Exposure: Skin and respiratory (asthma-like) conditions.

Health Hazards, Chronic: Reports have associated repeated or prolonged occupational exposure to solvents with permanent brain and central nervous system damage (sometimes referred to as Solvent or Painters Syndrome).

SECTION IV - FIRST AID MEASURES

Emergency and First Aid Procedures:

If Swallowed: Do not induce vomiting. Call a physician immediately. **Eye Contact:** Flush eyes with running water for at least 15 minutes. If irritation persists, obtain medical attention. **Skin Contact:** Flush thoroughly with cool water. Remove and wash contaminated clothing before reuse. **Inhalation:** If ill effects occur from breathing vapors, remove victim to fresh air and quiet and keep warm.
Sources Used: Raw material data, general toxicology from the trade for similar products.

SECTION V - FIRE FIGHTING MEASURES

Flammability: Combustible **Autoignition Temperature:** N. Ap.
Flash Point (method used): 105°F (40.6°C)
Flammable Limits: LEL 1.0% UEL N. Av
Extinguishing Media
Water? **Foam?** X **Water Fog?**
Alcohol Foam? **CO2?** X **Dry Chemical?** X
Vaporizing Liquid? **Other?**
Special Fire Fighting Procedures: Exclude air. Water hose stream may spread fire. Use water spray to keep containers cool.
Unusual Fire and Explosion Hazards: Vapors are heavier than air and may travel over distances to ignition sources (heat, flames, sparks, pilot lights, electric motors, etc.) where ignition may occur.
TDG Flammability Classification: Not known
Sensitivity to Mechanical Impact: None
Sensitivity to Static Discharge: Normal, for combustible liquid.

SECTION VI - ACCIDENTAL RELEASE MEASURES

Steps to be Taken in Case Material is Released or Spilled:
Extinguish all sources of possible ignition (flames, sparks, pilot lights, etc.) and provide ventilation. Dike and contain spill with inert material (sand, earth, etc.). Collect spill with absorbent material (example: floor-dri). Wash affected area with soap and water.

SECTION VII - HANDLING AND STORAGE

Precautions to be Taken in Handling and Storing:
Normal care in handling and storage. Do not store near heat or open flame.
Other Precautions: Keep out of reach of children.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection (Specify Types): Not normally required
Ventilation: **Local Exhaust:** Not required **Special:** Not required
Mechanical (General): Ventilate to maintain vapor level below TLV & PEL (listed in Section XI) **Other:** Not required
Protective Gloves: Natural rubber or synthetic.
Eye Protection: Approved safety goggles or glasses. **Footwear:** Not required
Other Protective Clothing or Equipment: Not required
Work/Hygienic Practices: Do not use in food handling or storage areas when food is present.

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: Mineral spirits 315°F (157°C) **pH:** N. Ap.
Specific Gravity (H2O) = 1: .772 **% Volatile:** > 99
Vapor Density (Air = 1): 4.90 **Odor Threshold:** N. Av.
Evaporation Rate (Butyl Acetate = 1): .12 **Oil/Water Distribution Coefficient:** N. Av.
Solubility in Water: Negligible
Vapor Pressure (MM HG): N. Av.
Melting Point: N. Ap.

SECTION X - STABILITY AND REACTIVITY

Stability: **Unstable:** **Stable:** X
Conditions to Avoid: N. Ap.
Incompatibility (materials to avoid): Strong oxidizers
Hazardous Decomposition or By-products: CO, CO₂, Various hydrocarbons
Hazardous Polymerization: **May occur:** **Will not occur:** X
Conditions to Avoid: N. Ap.

SECTION XI - TOXICOLOGICAL INFORMATION

Chemical	OSHA PEL	ACGIH TLV	Recom.	LD50	LC50
A	100 ppm	100 ppm	N. Av.	34,600 mg/kg	21,400 mg/M3, 4H

Teratogen, Mutagen, Reproductive Toxin Status: No
Toxicologically Synergistic Products: N. Av.

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicological Information: N. Av.
Chemical Fate Information: N. Av.

SECTION XIII - DISPOSAL CONSIDERATIONS

Waste Disposal Method:
Dispose of spilled material in accordance with local, state and federal regulations. (Incineration in an EPA authorized site is recommended)
RCRA Hazard Class: Unknown

SECTION XIV - TRANSPORT INFORMATION

Shipping Classification: paint (class 3.3)
UN Number: 1263
Packing Group: III

SECTION XV - PREPARATION DATA

Prepared By: Mike Tarvin
Telephone Number: 651-481-1900
Date: 10/06

SECTION XVI - REGULATORY INFORMATION

US Federal Regulations
TSCA Status: All ingredients listed.
CERCLA Reportable Quality: None
SARA Title III
Section 302 Extremely Hazardous Chemicals: None
Section 311/312 Hazard Category: Immediate health, chronic health, fire.
Section 313 Toxic Chemicals: None

State Regulations
NOTICE STATE OF CALIFORNIA
Warning: This product may contain chemicals known to the State of California to cause cancer or reproductive defects as trace impurities in the standard industrial materials used in the manufacture of this product.

International Regulations
WHMIS Controlled Product Hazard Class: B 3

SECTION XVII - OTHER INFORMATION

None
N. Ap. - Not Applicable; N. Av. - Not Available

NFPA SYSTEM

2 A. Health Hazard 2 A. Fire Hazard 0 A. Reactivity Hazard

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. MINUTEMAN INTERNATIONAL, INC. ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL.