

StainLess Seal

Stain Resistant Seal



A revolutionary seal that provides unique protection to floors.

Added Protection

StainLess provides greater protection to floors than conventional seals. Floors are protected by the stain resistant properties of StainLess from many substances that damage traditional floors.

A Healthcare Advantage

StainLess resists Povidone-Iodine staining common in health care facilities. It also resists urine, bodily fluids, rust, asphalt and many matting stains. StainLess can be used as a seal/finish in operating rooms where intensive staining is a persistent problem. It can also be used as a seal followed by application of a Multi-Clean finish.

Versatile Usage

StainLess is 100% acrylic and makes a great base for any Multi-Clean finish. It goes down smooth and easy, and fills porous flooring with maximum efficiency. Use everywhere a quality seal is required.

Low Odor Floor Care

If odors of floor care products are a problem, Multi-Clean has a solution:

- StainLess - Low Odor Floor Sealer
- Opti-Shine - High Performance, Low Odor Finish
- Stampede - Low Odor Stripper
- Century Maintenance - Neutral Cleaner, Citrus Scent.



StainLess exceeds slip resistance when tested according to ASTM D-2047. (James Machine)

Properties

Appearance	Milky, white emulsion
pH	7.3 - 8.3
Flashpoint	None
Non-Volatile (solids content)	16.5 - 17.5
Removability	Ultra Stripper
Coverage	1000 - 2500 sq. ft./gallon
Slip Resistance	Exceeds 0.5 min average static coefficient of friction (James Machine)
Drying Time	45 - 60 minutes
Minimum Application Temp	50°F
Storage Temperature	40°F minimum, 100°F maximum
Freeze - Thaw Stability	Passes 3 cycles
VOC (minus water)	0.7% (7 g/L)

VOC compliance:
EPA, CA, IL, IN, MI, OH, OTC, UT, and Canadian regulations.

Learn More.....at www.multi-clean.com

*Training materials: Multi-Clean Method Bulletin 1415 provides detailed floor care procedures.

*Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applicator. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.



600 Cardigan Road
Shoreview, Minnesota
Phone 651-481-1900
Fax 651-481-9987
Web www.multi-clean.com



Packaging

55 gallon, 904077
1 gallon, 904073