

Workhorse

Floor Finish



Description

Workhorse seal/finish offers an unbeatable combination of durability, gloss, and value. Workhorse is perfect for infrequent high speed or low speed maintenance and offers the versatility to meet multiple customer needs.

Features and Benefits

Versatility: One finish does it all! Works with all types of maintenance programs.

Simplicity: Use Workhorse as both a seal and a finish. Combine with Mustang Stripper and Century Maintenance Cleaner for a complete floor care program.

Performance: Workhorse holds up in heavy traffic and can be regularly burnished with propane, battery, or electric equipment.

Value: A great finish that fits every budget.

Directions for use: Use on vinyl composition and other resilient floors. For best results, strip worn finish. Apply up to four coats per day. If existing finish is in good condition, deep scrub with a blue or more aggressive pad, rinse and apply two coats of finish.



Workhorse exceeds slip resistance when tested according to ASTM D-2047. (James Machine)



Designed with black mark resistant technology!

Learn More.....at www.multi-clean.com

- *Training materials: Multi-Clean Method Bulletin 1415 provides detailed floor care procedures.
- *Calculators: Floor Care Project calculator provides estimates of product usage.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applicator. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.

Properties

Appearance	Milky white liquid
pH	8.6 ± .2
Specific Gravity.....	1.02 - 1.04
Flashpoint.....	None
Non-Volatile Content	18 ± .5
Slip Resistance.....	Exceeds .5 static coefficient
Classification	Semi-buffable
Coverage	2500 sq. ft./gallon
Drying Time	30 - 40 minutes
Minimum Application Temp.....	50°F
Storage Temperature.....	40°F min., 100°F max.
Freeze-Thaw Stability.....	Passes three cycles
Storage Stability	Excellent, 1 year

VOC Compliance - EPA, IL, IN, MI, OH, OTC, UT, and Canada regulations

Packaging

Size	Part No.
55 Gallon	904157
5 Gallon	904155



600 Cardigan Road
Shoreview, Minnesota
Phone 651-481-1900
Web www.multi-clean.com