

Dyno-Shine

Urethane Floor Finish



High Gloss And Durability

An aliphatic urethane fortified finish that provides superior gloss, durability, mark resistance, and adhesion. Its exceptional versatility makes it ideal for use with all maintenance programs (non-buff to ultra high-speed).

Works well on VCT, vinyl, terrazzo, concrete, quarry tile, cork, rubber, and laminate floors. Can also be used on synthetic gym floors.

- Optically Energized Non-Yellowing
- Combination Seal and Finish
- Excellent adhesion
- Fast-Drying - 30 Minutes Under Normal Conditions
- All Maintenance, All Surface Finish
- Slip-Resistant - Meets ASTM D2047

1. Thoroughly strip old seal, wax and finish from floors.
2. Apply thin coats of finish using a finish mop. Under normal conditions, allow to dry 30 minutes between coats. Buffing between coats is not necessary. For best results, apply a maximum of four coats in twenty four hours.
3. Maintain daily. Dust mop as often as required, but in all cases at least one time each day. Use a neutral cleaner to damp mop liquid spills as they occur. Damp mop or auto scrub daily with a no-rinse neutral cleaner. Burnish as needed.

Designed with black mark resistant technology!



Learn More.....at www.multi-clean.com
 *Training materials: Multi-Clean Method Bulletin 1415 provides detailed floor care procedures.
 *Calculators: Easy online calculator provides estimates of product usage for a project.



Aliphatic Urethane Fortified Finish

Properties

Type.....	Urethane/Acrylic Emulsion
Form.....	Opaque Liquid
Odor.....	Mild
Color.....	Milky White
Film Clarity.....	Clear
Weight Per Gallon.....	8.58 lbs.
pH.....	8.5-9.5
Storage Stability.....	Minimum one year
Freeze/Thaw.....	Passes 3 Cycles
V.O.C.....	0.3%
Floor Solids.....	22%
Coverage.....	2000 -3500 Sq.Ft./Gallon
Packaged	2 x 2.5 Gallon Case

Packaging

Size	Part no.
2x2.5 gallons	904506



600 Cardigan Road
 Shoreview, Minnesota
 Phone 651-481-1900
 Web www.multi-clean.com