

Opti-Shine

High Performance, Low Odor Finish



High Performance - Low Odor

Opti-Shine offers the performance of a highly cross-linked, durable floor finish without the objectionable odors during application. The *HP-LO Chemistry* used in this finish creates the optimum combination of high performance polymers with additives that do not produce unpleasant odors associated with traditional floor finish during the application process. Use Opti-Shine in hospitals, nursing homes, schools, class A office space, supermarkets and other retail stores.

Performance Matched 24/7

Opti-Shine is perfect for facilities that are high traffic or open 24 hours a day, 7 days a week. The fast drying, high solids formula produces a tough, vibrant shine with fewer coats resulting in less downtime. Exceptional durability can translate into less frequent recoats and stripping, saving time and labor. It can be applied at any time with confidence since Opti-Shine has a very pleasant scent with no objectionable odors. Multi-Clean's exclusive *SoilShield Technology* helps prevent premature discoloration of finishes due to soil embedment. Optical brighteners help give floors a dazzling gloss.

Maintenance Versatility

Opti-Shine can be easily burnished or spray buffed in high profile areas of a facility. Opti-Shine holds up to traffic and daily housekeeping sanitation programs, even in areas where frequent burnishing is not practical, such as hospital patient rooms.



Opti-Shine exceeds slip resistance standards when tested according to ASTM D-2047 (James Machine).

Designed with black mark resistant technology!



Learn More.....at www.multi-clean.com

- *Training materials: Multi-Clean Method Bulletin 1415 provides detailed floor care procedures.
- *Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applier. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.

Properties

Appearance	Milky white liquid
Finish Type	Extended wear
Non-Volatile (solids).....	25 ± .5%
pH	8.5 - 9.0
Weight/Gallon	8.61 - 8.68
Slip Resistance.....	Exceeds .5 static coefficient of friction
Coverage	2000 - 3000 sq. ft./gallon
Soil Resistance.....	Excellent
Drying Time	35 - 45 minutes
Color of Dry Film.....	Crystal clear
Application Temperature.....	50°F (minimum)
Storage Temperature.....	40°F minimum, 100°F maximum
Storage Stability	1 year under normal conditions
Freeze-Thaw Stability.....	Passes three cycles
VOC Compliant - VOC Free	

Packaging:

5 gallon BIB, 904245



600 Cardigan Road
Shoreview, Minnesota
Phone 651-481-1900
Web www.multi-clean.com