


Screen-Free Wood Floor Recoat Sealer



Bonding Agent

SCREEN-FREE Wood Floor Recoating Sealer allows Pro-Floor Extreme Gym Floor Coating to bond to most wood sports floors without the need to “screen” existing coatings. Traditionally, screening an existing floor coating is required to ensure that the top coat will bond to the existing coating and will not peel or flake off over time. This screening step is labor intensive and expensive when factoring in labor and cost of screens.

SCREEN-FREE saves time, labor and money plus ensures Pro-Floor Extreme will bond to most existing coatings*, with no risk of peeling or flaking issues. Just clean and scrub floor, remove any marks, rinse and apply one thin coat of SCREEN-FREE followed by one coat of Pro-Floor Extreme.

Summary of Directions

See detailed instructions in the Multi-Clean Wood Floor Method Bulletin 1420. This can be found at: <http://multi-clean.com/training.html>.

- Sweep and remove any debris on floor, including tape residue, gum etc.
- Clean floor using an autoscrubber or floor machine with a red pad and Hi-Trac at 8 - 16 oz/gallon.
- Dry scrub floor with 3M Surface Preparation Pads (SPP)
- Pick-up solution with autoscrubber or wet-vac.
- Rinse floor with fresh water. Scrub with red pad.
- Allow floor to dry.
- Apply one thin coat of Screen-Free.
- Allow floor to dry for one hour. If humidity is high, a slightly longer dry time may be required.
- Apply Pro-Floor Extreme according to instructions listed in Method Bulletin 1420.

* May not work on some epoxy-based sports floor coatings



Eliminates the need to screen wood sports floors before recoating.

Properties

Appearance	Milky white liquid
Odor.....	Mild
Coverage.....	2,000 -3,000 sq. ft./gallon
Number of Coats	1 coat
Dry Time	1 hour (more with high humidity)
Maximum Time before applying Pro-Floor Extreme	3 hours
Freeze-Thaw Stability.....	Passes three cycles
Storage Stability	1 year under normal conditions

FOR INDOOR USE ONLY.

Learn More.....at www.multi-clean.com

Training materials: Multi-Clean Method Bulletin 1420 provides detailed floor care procedures.
Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applier. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.



600 Cardigan Road,
Shoreview, Minnesota 55126
Phone 651-481-1900
Web www.multi-clean.com

Packaging

1 gallon, 905403