

FIRE-STORM

Super Strength Stripper



Description: Fire-Storm is the highest strength stripper available on the market today. Fire-Storm is designed to remove heavy finish buildups fast, leaving floors completely stripped the first time. Firestorm attacks and liquifies heavily burnished finishes without gumming up, making pickup of stripping solution easy with a wet dry vacuum or autoscrubber. Firestorm does not leave an alkali residue, so neutralizing is not necessary.

High Level of Actives

- Maximum Strength Available in a Stripper
- Fast and Complete Stripping of Finish
- Emulsified finish stays liquefied, doesn't gum up pads.
- Rinse Free – No Neutralizing Required

Directions:

1. For heavier build-up use 1 part Fire-Storm to 4 parts cool water.
For light to medium build-up, use 1 part Fire-Storm to 16 parts water.
2. Apply to a manageable area. (Caution: treated areas may become slippery).
3. Allow solution to react for 5 to 10 minutes - DO NOT ALLOW SOLUTION TO DRY ON FLOOR. Scrub with a floor machine or autoscrubber equipped with stripping pads. Doodle Bug around edges, etc.
4. Pick up spent solution with wet/dry vacuum or automatic scrubber.

Warning: Not for use on linoleum, asphalt tile or rubber tile floors. Wear water repellent/slip resistant footwear. Wear rubber gloves and safety eyewear to prevent skin/eye contact when using by hand. Ventilate enclosed areas to prevent excessive exposure to vapors.



Fire-Storm contains over 50% actives attack, penetrate and emulsify multiple coats of floor finish.

Properties

Appearance	Clear liquid
Odor.....	Lemon
% Active.....	50-55% by weight
pH (conc).....	11 - 12
pH (1:4).....	10.5 - 11.5
Dilutions.....	1:4 Heavy Stripping*
	1:16 Light Stripping*
Water Temp. (cool)	60-80°F
Storage Stability	1 year normal conditions
Freeze Thaw.....	Passes 3 cycles
Flash Point.....	> 146°F

*Fire-Storm is a cold water stripper.
DO NOT use warm or hot water.

VOC compliance:
EPA, CA, IL, IN, MI, OH, OTC, UT, and Canadian regulations.

Learn More.....at www.multi-clean.com

- Training materials: Multi-Clean Method Bulletin 1406 provides detailed floor care procedures.
- Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applicator. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.



600 Cardigan Road
Shoreview, Minnesota
Phone 651-481-1900
Web www.multi-clean.com

Packaging

1 gallon, 906933
5 gallon, 906935
55 gallon, 906937