

Dyno-Shine

Urethane Floor Finish



High Gloss And Durability

An aliphatic urethane fortified finish that provides superior gloss, durability, mark resistance, and adhesion. Its exceptional versatility makes it ideal for use with all maintenance programs (non-buff to ultra high-speed).

Works well on VCT, vinyl, terrazzo, concrete, quarry tile, cork, rubber, and laminate floors. Can also be used on synthetic gym floors.

- **Durability:** Urethane delivers unsurpassed black mark and scuff resistance keeping floors looking great.
- **Burnish Response:** Dyno-Shine produces a wet look shine with electric, battery and propane equipment.
- **Flexibility:** Dyno-Shine can be used on softer surfaces including cork, rubber, and synthetic sports floors.
- **Adhesion:** Dyno-Shine offers better adhesion to concrete, terrazzo, and laminate floors.
- **Optically Energized:** Dyno-Shine is a non-yellowing finish with enhanced brighteners.

1. Thoroughly strip old seal, wax and finish from floors.
2. Apply thin coats of finish using a finish mop. Under normal conditions, allow to dry 30 minutes between coats. Buffing between coats is not necessary. For best results, apply a maximum of four coats in twenty four hours.
3. Maintain daily. Dust mop as often as required, but in all cases at least one time each day. Use a neutral cleaner to damp mop liquid spills as they occur. Damp mop or auto scrub daily with a no-rinse neutral cleaner. Burnish as needed.

Designed with black mark resistant technology!



Learn More.....at www.multi-clean.com
 *Training materials: Multi-Clean Method Bulletin 1415 provides detailed floor care procedures.
 *Calculators: Easy online calculator provides estimates of product usage for a project.



Dyno-Shine exceeds slip resistance standards when tested according to ASTM D-2047 (James Machine).

Properties

Type.....	Urethane/Acrylic Emulsion
Form.....	Opaque Liquid
Odor.....	Mild
Color.....	Milky White
Film Clarity.....	Clear
Weight Per Gallon.....	8.58 lbs.
pH.....	8.5-9.5
Storage Stability.....	Minimum one year
Freeze/Thaw.....	Passes 3 Cycles
V.O.C.....	0.3%
Floor Solids.....	22%
Coverage.....	2000 -3500 Sq.Ft./Gallon
Packaged	2 x 2.5 Gallon Case
Dry time.....	30 minutes

Packaging

Size	Part no.
2x2.5 gallons	904506



600 Cardigan Road
 Shoreview, Minnesota
 Phone 651-481-1900
 Web www.multi-clean.com