

Pro-Floor® Extreme

Waterborne Gym Finish



Durable Urethane Finish

Pro-Floor Extreme is a waterborne urethane based finish providing extreme durability and traction on all wood gym, racquetball or sports floors. Pro-Floor Extreme resists scratching, scuffing, and black marking better and longer than other finishes. Pro-Floor Extreme uses a crosslinker catalyst added for extra durability. You won't find a product that will hold its shine longer!

Exceptional Clarity and Shine

The clarity of Pro-Floor Extreme allows for the natural color and beauty of wood flooring to show. Pro-Floor Extreme exhibits a deep shine comparable to oil-based products without darkening the wood. For best performance and gloss retention, maintain Pro-Floor Extreme using Hi-Trac at 4 oz per gallon and an autoscrubber equipped with a White Pad.

Goes Down Fast and Easy

Pro-Floor Extreme is self-leveling and does not bubble or foam like many competitive finishes and goes down fast and easy with the Padco Professional Floor Coater.

Pro-Floor Extreme is ready for activity in as little as 24 hours. This means that preparation and coating can be done in a single day, eliminating lengthy downtime.

NOTE: Some parquet floors should not be finished with polyurethane coatings. Check with floor manufacturer before using on parquet floors.



2011 WNBA Champions - Minnesota Lynx. Target Center floor coated with Pro-Floor Extreme April 2010.

Properties

Appearance	Milky white liquid
Odor	Mild
% Solids (no catalyst)	28%
% Solids (catalyzed)	30%
Coverage	700-900 sq. ft./gallon
Slip Resistance	Exceeds 0.5 min. ASTM D2047
Dry Time	3 hours to Recoat 24 hours to resume activity
VOC (minus water)	Less than 275 grams/liter
Sward Hardness	40 - after 7 days
Chemical Resistance:	No effect: Ethyl alcohol, Isopropyl alcohol, Coffee, Colas, Soda

Learn More.....at www.multi-clean.com

Training materials: Multi-Clean Method Bulletin 1420 provides detailed floor care procedures. Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applicator. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.



600 Cardigan Road
Shoreview, Minnesota
Phone 651-481-1900
Fax 651-481-9987
Web www.multi-clean.com

VOC Compliant Low Odor



Packaging

1 gallon, 909253
(Catalyst is included)