

# PowerBulk

Our Chemistry - Your Water

**Formula 340** is a heavy-duty, low-foaming Industrial strength degreaser formulated to attack grease and grime. It is recommended for cleaning concrete floors and other areas where heavy-duty industrial degreasing is required.

- Spontaneously emulsifies oily soil - works fast; effective in any automatic scrubbers.
- Contains NO solvents - safer for workers and the environment
- Innovative formula - produces better cleaning while saving time and labor
- Low Foaming Degreaser. Any foam that is generated in recovery tanks will break quickly, so it will not build-up.
- Meets USDA Performance Standards for A-1 type products.

*Use only on surfaces resistant to alkaline cleaners. Aluminum, floor finish and other sensitive surfaces may be adversely affected.*



PowerBulk is a unique system of highly soluble super concentrated matched liquid components. When mixed with local water, these components produce full strength products.

### Starter Kit:

Get started with this program, a starter kit is available that includes 5 gallon Bag-in-Boxes of super concentrate and a new 55 gallon plastic drum. Each starter kit comes with enough chemical to make 55 gallons of ready-to-sell concentrate.

Kit No	Product	Description
909925	Formula 340	1 BIB each Part A & B
909975	Fury	1 BIB each Part A & B
909935	Tough Green	2 BIB's of PB Tough Green



### Rapid Station

Dispenses RTU solutions of cleaners or degreasers from 55 gallon drums directly into autoscrubbers or mop buckets at 10gpm.



600 Cardigan Road  
Shoreview Minnesota  
Phone 651-481-1900  
www.multi-clean.com

# Formula 340

## Heavy Duty Degreaser



### Directions:

- 1) Obtain a 55 gallon drum, place it near a water source. Feed water hose into drum bung hole until it touches bottom.
- 2) Turn on water and while water is running, use a funnel and pour all of Part "A" and then all of Part "B" into the drum.
- 4) Turn off water when level is about an inch from the top of drum. Apply product label to drum and file SDS for reference.

### Properties of 55 Gallon Concentrate

**Appearance:** Orange Liquid  
**Odor:** Mild Odor, No Fragrance Added  
**pH** (concentrated/1%): > 13 (Concentrated) / 11-12 (1%)  
**Density** (lb./gal.): 8.6  
**Hard Water Tolerance:** Yes  
**Stability:** Warranty 1 year at ambient temperature  
**Freeze/Thaw Stability:** OK, 3 cycles  
**D.O.T. Hazard Class/ID No.:** Corrosive Liquid, Basic Inorganic, N.O.S. (Potassium Hydroxide), UN 3266, Class 8  
**Flashpoint** (TCC): None  
**Dilutions:**  
 • Light soil: 1 - 2 oz./gal. (8-15 ml/L)  
 • Heavy Soil: 4-6 oz./gal. (30-45 ml/L)

### HMIS Hazard Rating for Concentrate

Health	2	0-Least
Flammability	0	1-Slight
Reactivity	0	2-Moderate
Personal Protection	X	3-High
		4-Extreme

### Packaging

Pack: 909915  
Includes: Part A & B  
 Starter Kit: 909925  
Includes: Empty Drum, Part A & B



14N845 US Route 20  
Pingree Grove IL  
Phone 847-264-5400  
www.powerboss.com